Data Sheet

We make sure



Issue April 2008

LIFEBOOK S6410 Get ready for your next business trip

Pages 4

The exclusive LIFEBOOK S6410 is your best friend on the move, leaving no compromises!

The sturdy notebook keeps the balance between low weight, best connectivity, high-end performance and modularity. With its integrated UMTS/HSUPA, ConfCamera and brilliant 13.3-inch wide display, you are going to experience true mobility – anywhere, anytime.

The combination of performance, modularity and flexibility gives you the functionality and ease of use of a full-sized PC. Intel® Centrino® Duo Mobile Technology with latest Intel® GM965 chipset technology delivers high performance and Business-day-long independency from the power socket.

This notebook is designed for highest quality with extensive testing and an extra-strong magnesium lid.

Elegance

Designed for the most demanding mobile users, LIFEBOOKs are the perfect synthesis of form, function and style.

- Light-weight modular 13.3-inch wide notebook with only 1.7 kg
- Exclusive protective leather bag
- Modular bay fitting an optical disk drive or battery
- Excellent resolution and video quality

Ergonomics

- 13.3-inch WXGA -display for maximum viewing comfort
- Convenient working with full sized keyboard
- Small in size but great expandability with maximum ports
- Eco Button to extend battery life by powering down energy consumption

Connectivity

- Bluetooth and Wireless LAN optional integrated
- Optional Port Replicator for easy connection to all your peripherals, compatible with LIFEBOOK E Series and LIFEBOOK C Series
- Long lasting battery for Business-day long independency with first and second battery

Security

- Trusted platform module (TPM 1.2) provides more secure applications and makes transitions safe
- Biometric fingerprint sensor
- Built-in SmartCard controller and optional SmartCase Logon+: software with best integration into your IT
- Lock workstation Button for fast sign off the system

Reliability

- Highest quality design with magnesium lid
- Hard disk drive ShockSensor minimizes data loss and guarantees a higher reliability of your data
- Spill-proof keyboard offers protection against system damage

Manageability

- Integrate the bundled system management software Desk View Admin in every common IT infrastructure
- Seamless integration in heterogeneous enterprise management systems
- Get optional add on packages: With DeskView Migrate and DeskView Control for e.g. migration projects and extensive client lifecycle management tasks













System	LIFEBOOK S6410
Processor	
Intel® Core™2 Duo Processor Second level cache	T7100 (1.8GHz) 2 MB
Front side bus (FSB)	800 MHz
	T7300 (2.0GHz)
Intel® Core™2 Duo Processor	T7500 (2.2GHz) T7700 (2.4GHz)*
Second level cache	4 MB
Front side bus (FSB)	800Mhz
Intel® Core™2 Duo Processor	T8100 (2.1GHz)
Second level cache	T8300 (2.4GHz) 3 MB
Front side bus (FSB)	800Mhz
Intel® Core™2 Duo Processor	T9300 (2.4GHz)
Second level cache	T9500 (2.5GHz) 6 MB
Front side bus (FSB)	800Mhz
Chipset	
Northbridge Southbridge	Intel® GM965 ICH 8-M
Memory	1011 0-101
DIMM slots	2
DDR2-667 SDRAM, 667 MHz BIOS	up to 4GB
BIOS Flash EPROM	BIOS based on Phoenix TrustedCore Notebook
Interfaces	
SIM card slot	1
Infrared link (Fast IrDa 1.1, 4 Mbps) Type I/II PC Card slot	1
Memory card slot (SD, MS, xD and MSPRO)	1
USB 2.0	3
S-Video out (TV-out) without adapter cable VGA	1
Modem RJ-11	1
LAN RJ-45	1
Audio-in (line-in / microphone) Audio-out (line-out / headphone)	1
DC-in	1
IEEE1394	1
Kensington Lock Docking connector for Port Replicator	1 1
Port Replicator interfaces (optional):	
USB 2.0	4
VGA	1
DVI-D	(with HDCP support)
Serial port Parallel port	1
LAN RJ-45	1
PS/2	1
DC-in Microphone	1
Headphone	1
Power on switch	1
Kensington Lock Camera	Built-in ConfCamera (1,3 megapixle VGA Camera)
Modem on board	Built in Comodinata (1,6 magapiate volvounicia)
56K V.92 modem MDC1.5	1
LAN on board built-in 10/100/1000 Mbps Marvell 88E8055	x
Wireless Technologies (WLAN)	^
Import and usage according to country-specific regulations.	
3 Dual band WLAN antennas, 2 UMTS antennas Intel® Wireless WiFi Link 4965AGN	optional
Atheros Minicard b/g 802.11 b/g	optional
WiFi certified	X Optional (downlink 7.2 unlink 2.0)
Integrated UMTS/HSUPA, also supported are GPRS and EDGE or higher Bluetooth	Optional (downlink 7.2, uplink 2.0)
Bluetooth V2.0	optional
Audio	
Stereo speakers Sound chip	X RealTek ALC262
Internal microphone	2
Keyboard and pointing device	Co. Warrant Land
Keyboard	Spill proof keyboard, 85 keys, 19mm pitch,
Tioyadaru	3mm key stroke
Touchpad	with two mouse buttons, scroll via fingerprint sensor
Fingerprint sensor Launch Keys	X
Application Buttons	4
Lock workstation Button	X
Mobility Center Button	X
Eco Button	X

Souther Purson Capaphics Intel® X3100 integrated graphics X Charles X Charles X Charles X Charles X X Ch	ID 0."	
Graphics Intel® X310 integrated graphics Intel® X10 X (Q4/2007) Preschader 3.0 X (Q4/2007) Proschader 4.0 X (Q4/2007) Proschader 4.0 X (Q4/2007) Proschader 4.0 X (Q4/2007) Proschader 5.0 X (Q4/2007)	Recovery Button	Х
Intel® X3100 integrated graphics		X
Direct XIS		
Direct X10		X
Placehaber 3.0 X (O-42007) Doubler (Windows XP & Windows Vista) X (O-42007) Doubler (Windows XP & Windows Vista) X (O-42007) X (O-42	Direct X9	X
Pueshaber 4.0 X (CA2007)	Direct X10	x (Q4/2007)
Deather (Windows XP & Windows Vista) X X X X X X X X X	Pixelshader 3.0	X
Deather (Windows XP & Windows Vista) X X X X X X X X X	Pixelshader 4.0	x (Q4/2007)
13.3-inch FFT WXRA 17.280 x 900 pixel, glare display Mark resolution for external displays 1920 x 1200 / true color / 60 Hz (bdd) Wax resolution for external displays 1920 x 1200 / true color / 60 Hz (bdd) Wax 1200 / true color / 60 Hz (bdd) Wax 1200 R SATA 150 (5400 pm) X X 100 G BS ATA 150 (5400 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 S GB SATA 150 (7200	DualView (Windows XP & Windows Vista)	X
13.3-inch FFT WXRA 17.280 x 900 pixel, glare display Mark resolution for external displays 1920 x 1200 / true color / 60 Hz (bdd) Wax resolution for external displays 1920 x 1200 / true color / 60 Hz (bdd) Wax 1200 / true color / 60 Hz (bdd) Wax 1200 R SATA 150 (5400 pm) X X 100 G BS ATA 150 (5400 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G BS ATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 G GB SATA 150 (7200 pm) X X 100 S GB SATA 150 (7200		
Max. resolution for external displays		X
Hard disk drives (internal)		
S.M.A.R.T. 8. CB.S.A.T.A.150 (S400 pm) 8. CB.S.A.T.A.150 (S400 pm) 8. CB.S.A.T.A.150 (S400 pm) 9. CB.S.A.T.A.150 (S400 pm) 160 GB.S.A.T.A.150 (S400 pm) 170 Supported Standard (S4		1020 X 1200 / trad 00101 / 00 112 (tbd.)
ShockSensor for HDD shock protection 30 GB SATA 150 (5400 pm) 120 GB SATA 150 (5400 pm) 121 GB SATA 150 (5400 pm) 121 GB SATA 150 (5400 pm) 122 GB SATA 150 (5400 pm) 123 GB SATA 150 (5400 pm) 124 GB SATA 150 (5400 pm) 125 GB SATA 150 (5400 pm) 126 GB SATA 150 (5400 pm) 127 GB SATA 150 (5400 pm) 128 GB SATA 150 (5400 pm) 129 GB SATA 150 (5400 pm) 120 GB SATA 150 (5400 pm) 120 GB SATA 150 (5400 pm) 120 GB SATA 150 (5400 pm) 121 GB SATA 150 (5400 pm) 122 GB SATA 150 (5400 pm) 123 GB SATA 150 (5400 pm) 124 GB SATA 150 (5400 pm) 125 GB SATA 150 (5400 pm) 126 GB SATA 150 (5400 pm) 126 GB SATA 150 (5400 pm) 127 GB SATA 150 (5400 pm) 128 GB SATO (5400 pm) 128 GB S		V
80 GB S-ATA 150 (5400 pm) 100 GB S-ATA 150 (5400		
120 GB S-ATA 150 (5400 pm) X X X X X X X X X		
180 GB S-ATA 150 (5400 (pm) 100 GB S-ATA 150 (7500 (pm) 100 GB S-ATA 150 (
180 GB S-ATA 150 (7200 (mm) 64 GB Solid State Disk 7 Gbyte equals one billion bytes, when referring to hard disk drive capacity, accessible capacity may vary, also depending on used software Modular Prives		
Section Solid State Disk X Clayte equate on bellion bytes, when referring to hard disk drive capacity, accessible capacity accessible acces		Х
1 Citype equals one billion bytes, when referring to hard disk drive capacity; accessible capacity any ava, also depending on used software and tool. More information in specific Data Sheet high provision of the provision of t		Х
capacity accessible capacity may vary, also depending on used software and tool. Modular Drives DVD super-multi drive incil. RAM Modular Drives DVD super-multi drive incil. RAM Manageability Please refer to http://www.fujisus-simens.com/optical_drives/ Manageability Please refer to http://www.fujisus-simens.com/optical_drives/ Manageability Please refer to http://www.fujisus-simens.com/optical_drives/ Modular Supported Sandard Supported Sandard Supported Sandard Supported Sandard WMI / CIM / WBEM PMI / CIM / WBEM		X
and tool. Modular Drives DVD super-multi drive incit. RAM More information in specific Data Sheet Intip//www.fullsus-alterners.com/optical_drives/ Intip//www.fullsus-alterners.com/opt		
Modular Drives X	capacity; accessible capacity may vary, also depending on used software	
DVD super-multi drive incit. RAM More information in specific Data Sheet. http://www.fujitsu-siemena.com/optical drives/ Minangeability/ Please refer to http://www.fujitsu-siemena.com/optical drives/ Minangeability/ Please refer to http://www.fujitsu-siemena.com/optical drives/ Minangeability/ Please refer to http://www.fujitsu-siemena.com/optical drives/ Supported Standard WMI / CIM / WBEM PKE Security Physical security Physical security Physical security Physical security System Society Security System Society Society Society Society Society Society Society Society Value and supervisor BIOS password System Society User and supervisor BIOS password System Lock BIOS SharaCard security x Values and supervisor BIOS password System Lock BIOS SharaCard security Values and supervisor BIOS password System Lock BIOS SharaCard security Values and supervisor BIOS password System Lock BIOS SharaCard security Values and supervisor BIOS password System Lock BIOS SharaCard security Values and supervisor BIOS password Values and supervisor BIOS password System Lock BIOS SharaCard security Values and supervisor BIOS password Values B	and tool.	
More information in specific Data Sheet http://www.fujisus-siemens.com/poticul.rivries/ Managability Please refer to http://www.fujisus-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefin der. futni Supported Standard WMI / CIM / WBEM	Modular Drives	
More information in specific Data Sheet http://www.fujisus-siemens.com/potitodi.or/indrastructure_solutions/manageability Please refer to http://www.fujisus-siemens.com/solutions/it_infrastructure_solutions/manageability/featurefin der. fittin Supported Standard WMI / CIM / WBEM		X
http://www.fujitsu-siemens.com/optical_drives/ Manageability. Please refer to http://www.fujitsu-siemens.com/southons/funifastructure_solutions/manageability/featurefin der. Intral Supported Standard Supported Standard WMI / CIM / WBEM		
Managabality Please refer to http://www.flujisu-siemens.com/solutions/i_infrastructure_solutions/manageability/featurefin der.html Supported Standard	http://www.fujitsu-siemens.com/ontical_drives/	
Please refer to http://www.fujitsus-siemens.com/southions/fi_infrastructure_solutions/fi_infrastructure_solutions/manageability/featurefin der.html Supported Standard		
semens.com/solutions/fi.infrastructure_solutions/manageability/leaturefin der.html Supported Standard WMI / CIM / WBEM PXE X X BOORD BOORD Security Physical security Physical security Physical security Rensington Lock support System Socurity System Socurity Bot select virus protection Trusted Platform module 1.2 optional Symantee Norton Internet Security User sacruity User sacruity User and supervisor BIOS password System Lock BIOS SmartCard security Y X User and supervisor BIOS password System Lock BIOS SmartCard security Y X System Lock BIOS SmartCard Smart		
Description Company		
Supported Standard		
Security		
PXE		
BootP Security Physical security Kensington Lock support System Security Boot sector virus protection Trusted Platform module 1.2 Symantec Norton Internet Security User and supervisor BIOS password System Lock BIOS SmartCard security Was Security User and supervisor BIOS password System Lock BIOS SmartCard security Hard disk password Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCase Logon+ Incl. Fingerprint Software Power supply 1st Li-Ino battery for cell 5200mAh (24.8Wh) (Option) 1st Li-Ino battery for cell 5200mAh (24.8Wh) 1st L	WMI / CIM / WBEM	X
Security Physical security Kensington Lock support System Security System Lock BIOS SmartCard security X System Lock BIOS SmartCard security X X System Lock BIOS SmartCard controller in PC Card with system lock support X X System Lock BIOS SmartCard Controller in PC Card with system lock support X X	PXE	X
Physical security	BootP	made4you
System Security Soot sector virus protection - -	Security	
Kensington Lock support System Security Soot sector virus protection -	Physical security	
System Security South Security South Security South Security Symanec Notron Internet Security X X X X X X X X X		X
Boot sector virus protection Trusted Platform module 1.2 Symantes Notron Internet Security User Security User and supervisor BIOS password System Look BIOS SmartCard security Hard disk password Integrated Fingerprint Sensor Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCasc Logonn- Incl. Fingerprint Software Power supply 3ts Li-John battery 6 cell 5200mAh (63.3 Wh) 2nd Li-Ion battery 6 cell 5200mAh (24.8 Wh) (Option) First 1-4 Second battery "(Mobile Mark 2005) (up to) 18 h First 1-4 Second battery "(Mobile Mark 2005) (up to) 19 (wholie Mark 2005) (up to) 10 (14.4 Wholie Mark 2005) 11.4 h AC adapter 1904/80W Adapter Rated voltage (AC input) 100 - 240 V Rated firequency 50 - 60 Hz DC output 19 V, 4.22 Operating temperatures Relative humidity (non-condensing) Ambient temperature Dimensions (Neight Dimensions (Weight Dimensions (Weight Dimensions (Weight Dimensions (Weight Weight' Neight may vary depending on actual configuration Certificates CE Marking CE According to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE1 (Wireless) X (with integrated WLAN) CE1 (Wireless) X (with integrated WLAN) CE1 (Certificates CE Generic Report X (CE1 (Certificates) CE (CE1 (Certificates) CE1 (Certificates) CE		"
Trusted Platform module 1.2 Symantec Notron Internet Security User Security User and supervisor BIOS password SystemLock BIOS SmartCard security Hard disk password Integrated Fingerpint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCase Logon+ incl. Fingerprint Software Power supply 1st Li-Ion battery 6 cell 5200mAH (53.3 Wh) 2nd Li-Ion battery 6 cell 5200mAH (53.3 Wh) 2nd Li-Ion battery 6 cell 2300mAH (24.8 Wh) (Option) 1st Li-Ion battery 6 cell 2300mAH (24.8 Wh) (Option) 1st Li-Ion battery 6 cell 2300mAH (24.8 Wh) (Option) 1st Li-Ion battery 6 cell 2300mAH (24.8 Wh) 2nd Li-Ion battery 6 cell 23		
Symantec Norton Internet Security User and supervisor BIOS password System Look BIOS SmartCard security Hard disk password Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCase Logone incl. Fingerprint Software Power supply 18 Li-John battery 6 cell 5200mAH (53.3 Wh) 2nd Li-Ion battery 6 cell 5200mAH (24.8Wh) (Option) 18 Li-Lon battery 6 cell 2300mAH (24.8Wh) (Option) 18 Li-Lon battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 19 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 10 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 10 St Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 11 Li-John battery 6 cell 2300mAH (24.8Wh) (Option) 11 Li-John battery 6 cell 2300mAH (24.8Wh) 12 St Li-John battery 6 cell 2300mAH (24.8Wh) 13 Li-John battery 6 cell 2300mAH (24.8Wh) 14 Li-John battery 6 cell 2300mAH (24.8Wh) 15 Li-John battery 6 cell 2300mAH (24.8Wh) 16 St Li-John battery 6 cell 2300mAH (24.8Wh) 17 Li-John battery 6 cell 2300mAH (24.8Wh) 18 Li-John battery 6 cell 2300mAH (24.8Wh) 18 Li-John battery 6 cell 2300mAH (24.8Wh) 19 Li-John battery 6 cell 2300mAH (24.8Wh) 11 Li-John battery 6 c		ontional
User and supervisor BIOS password SystemLock BIOS SmartCard security Hard disk password Integrated Fingerprint Sensor Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support SmartCase Logon+ incl. Fingerprint Software Power supply 1st Li-lon battery 6 cell 5200mAH (53.3 Wh) 2nd Li-lon battery 6 cell 5200mAH (53.3 Wh) 2nd Li-lon battery 6 cell 5200mAH (53.3 Wh) 2nd Li-lon battery 6 cell 2300mAH (53.3 Wh) 2nd Li-lon battery 6 cell 2300mAH (53.3 Wh) 2nd Li-lon battery 6 cell 2300mAH (24.8Wh) (Option) First + Second battery (Mobile Mark 2005) 11.4 h Ac adapter 19/80W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 19 V, 4.22 DC output 19 V, 4.22 DC output 19 V, 4.22 Do Joperating temperatures Relative humidity (non-condensing) Ambient temperature So - 35° C Dimensions (I k W x D) 314 x 234 x 22.7 - 31.5 mm Dimensions (I k W x D) Weight User Sounding to EU Directives 88/336/EEC (EMC) 27.323/EEC (Forduct safety) CE according to EU Directives 88/336/EEC (EMC) 27.323/EEC (Forduct safety) CE according to 99/5/EEC (R&TTE) CEI (Wireless) CE (Gorman ergonomic approval) UL/cUL CB Generic Report CB (Sigeman ergonomic approval) CB (Sigeman ergonomic approval) CB (Si		-
User and supervisor BIOS password		X
SystemLock BIOS SmartCard security		
Hard disk password	User and supervisor BIOS password	X
Integrated Fingerprint Sensor	SystemLock BIOS SmartCard security	X
Integrated SmartCard controller in PC Card with system lock support SmartCase Logon+ incl. Fingerprint Software		X
SmanCase Logon+ incl. Fingerprint Software x	Integrated Fingerprint Sensor	Х
SmanCase Logon+ incl. Fingerprint Software x	Integrated SmartCard controller in PC Card with system lock support	χ
Power supply		-
st Li-lon battery 6 cell 5200mAh (53.3 Wh) Options		··
2nd Li-lon battery & Cell 2300mAh (24.8Wh) (Option)		
First battery * (Mobile Mark 2005) [up to] First + Second battery * (Mobile Mark 2005) AC adapter 19V/80W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 19 V, 4.22 Operating temperatures Relative humidity (non-condensing) Ambient temperature Pimensions / Weight Dimensions / Weight Dimensions (H x W x D) Weight* *Weight may vary depending on actual configuration Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE (Emission/Immunity) CE (Emission/Immunity) CE (Emission/Immunity) CE (Emission/Immunity) CE (SG (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) CB Generic Report CB (Safety) CB (S		ontional
First + Second battery * (Mobile Mark 2005)		
AC adapter 19V/80W Adapter Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 19 V, 4.22 Departing temperatures Relative humidity (non-condensing) Ambient temperature Dimensions / Weight Dimensions (Weight Dimensions (H x W x D) Weight* 'Weight may vary depending on actual configuration Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE (CE (Wireless) CE (Emission/Immunity) R&TTE CE (Wireless) CE (Emission/Immunity) R&TTE SG (German ergonomic approval) UL/cUL CB Generic Report CB (Safety)		
Rated voltage (AC input) 100 - 240 V Rated frequency 50 - 60 Hz DC output 19 V, 4.22		11. 4 N
Rated frequency 50 - 60 Hz DC output 19 V, 4.22		
Rated frequency 50 - 50 Hz DC output 19 V, 4.22 Operating temperatures Relative humidity (non-condensing) Ambient temperature 5° - 36° C Dimensions / Weight Dimensions / Weight Dimensions (H x W x D) Weight may vary depending on actual configuration Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE (Wireless) CE (Emission/Immunity) R&TTE FCC S(German ergonomic approval) UL/cUL CB Generic Report CB (Safety) CB (Safety) X CB (Safety)		X
Relative humidity (non-condensing) Ambient temperature Relative humidity (non-condensing) Ambient temperature Dimensions / Weight Dimensions (H x W x D) Weight* * Weight may vary depending on actual configuration Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) X CE! (Wireless) X (with integrated WLAN) CE (Emission/Immunity) X R&TTE FCC GS (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) CB (Safety) X		
Rélative fumidity (non-condensing) Ambient temperature Dimensions / Weight Dimensions (H x W x D) Weight To weight Dimensions (H x W x D) Weight may vary depending on actual configuration Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE! (Wireless) CE! (Wireless) CE (Emission/Immunity) X R&TTE X FCC GS (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) ROHS WHOL TBR21 Energy Star Wiric certified Operating System Microsoft Windows XP Professional		
Ambient temperature Dimensions / Weight Dimensions (H x W x D) Weight * 314 x 234 x 22.7 – 31.5 mm		
Dimensions / Weight 314 x 234 x 22.7 − 31.5 mm Weight* 1,75 kg * Weight may vary depending on actual configuration x Cetificates x CE according to EU Directives 89/336/EEC (EMC) x 73/23/EEC (Product safety) x CE according to 99/5/EEC (R&TTE) x CE! (Wireless) x (with integrated WLAN) CE (Emission/Immunity) x R&TTE x FCC - GS (German ergonomic approval) tbd UL/cUL x CB (Safety) x ROHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System Microsoft Windows XP Professional Microsoft Windows Vista ^{TIM} x		
Dimensions (H x W x D)		5° - 35° C
Dimensions (H x W x D)	Dimensions / Weight	
Weight * Weight may vary depending on actual configuration Certificates CE Marking		314 x 234 x 22.7 – 31.5 mm
*Weight may vary depending on actual configuration Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE (Emission/Immunity) X R&TTE FCC GS (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) ROHS WHQL TBR21 Energy Star WiFi certified Operating System Microsoft Windows XP Professional Microsoft Windows XP Professional Microsoft Windows Vista TM X X X X X X X X X X X X X		
Certificates CE Marking CE according to EU Directives 89/336/EEC (EMC) 73/23/EEC (Product safety) CE according to 99/5/EEC (R&TTE) CE! (Wireless) CE (Emission/Immunity) R&TTE FCC GS (German ergonomic approval) UL/cUL CB Generic Report CB (Safety) ROHS WHQL TBR21 Energy Star WiFi certified Operating System Microsoft Windows XP Professional Microsoft Windows Vista™ M X X X X (with integrated WLAN) X X X X X X X X X X X X X		·,· · · ·· 9
CE Marking x CE according to EU Directives 89/336/EEC (EMC) x 73/23/EEC (Product safety) x CE according to 99/5/EEC (R&TTE) x CE! (Wireless) x (with integrated WLAN) CE (Emission/Immunity) x R&TTE x FCC - GS (German ergonomic approval) tbd UL/cUL x CB Generic Report x CB (Safety) x ROHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System Microsoft Windows XP Professional driver support Microsoft Windows Vista™ x		
CE according to EU Directives 89/336/EEC (EMC) X 73/23/EEC (Product safety) X CE according to 99/5/EEC (R&TTE) X CE! (Wireless) X (with integrated WLAN) CE (Emission/Immunity) X R&TTE X FCC - GS (German ergonomic approval) tbd UL/cUL X CB Generic Report X CB (Safety) X ROHS X WHQL X TBR21 X Energy Star X WiFi certified X Operating System Microsoft Windows XP Professional driver support Microsoft Windows Vista TM X		v
73/23/EEC (Product safety) x CE according to 99/5/EEC (R&TTE) x CE! (Wireless) x (with integrated WLAN) CE (Emission/Immunity) x R&TTE x FCC - GS (German ergonomic approval) tbd UL/cUL x CB Generic Report x CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System Microsoft Windows XP Professional driver support Microsoft Windows Vista™ x		X
73/23/EEC (Product safety)		X
CE! (Wireless) x (with integrated WLAN) CE (Emission/Immunity) x R&TTE x FCC - GS (German ergonomic approval) tbd UL/cUL x CB Generic Report x CB (Safety) x ROHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System driver support Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x		
CE (Emission/Immunity) x R&TTE x FCC - GS (German ergonomic approval) tbd UL/cUL x CB Generic Report x CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System driver support Microsoft Windows VP Professional driver support Microsoft Windows Vista TM x		
R&TTE X FCC - GS (German ergonomic approval) tbd UL/cUL X CB Generic Report X CB (Safety) X ROHS X WHQL X TBR21 X Energy Star X WiFi certified X Operating System Microsoft Windows XP Professional Microsoft Windows Vista TM driver support Microsoft Windows Vista TM X		
FCC GS (German ergonomic approval) UL/CUL X CB Generic Report CB (Safety) RoHS X WHQL TBR21 Energy Star WiFi certified Operating System Microsoft Windows XP Professional Microsoft Windows Vista TM		-
GS (German ergonomic approval) tbd UL/cUL x CB Generic Report x CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System driver support Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x		X
UL/cUL x CB Generic Report x CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System x Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x		•
UL/cUL x CB Generic Report x CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System x Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x	GS (German ergonomic approval)	tbd
CB Generic Report x CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System x Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x		Х
CB (Safety) x RoHS x WHQL x TBR21 x Energy Star x WiFi certified x Operating System x Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x	_	-
RoHS		-
WHQL x TBR21 x Energy Star x WiFi certified x Operating System x Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x		-
TBR21 x Energy Star x WiFi certified x Operating System x Microsoft Windows XP Professional driver support Microsoft Windows Vista TM x	_	
Energy Star x WiFi certified x Operating System Microsoft Windows XP Professional Microsoft Windows Vista™ driver support X x		-
WiFi certified x Operating System driver support Microsoft Windows XP Professional driver support Microsoft Windows Vista™ x	-	-
Operating System Microsoft Windows XP Professional driver support Microsoft Windows Vista™ x		-
Microsoft Windows XP Professional Microsoft Windows Vista™ x driver support x	Operating System	X
Microsoft Windows Vista™ x · · ·		data and a second
		- · · · · · · · · · · · · · · · · · · ·
Microsoft Windows Vista® Business/ Microsoft Windows XP® x		

Professional TwinLoad	
Software (compatibility / preinstalled)	
Adobe Acrobat Reader	X
Application panel tool	X
Camera	X
Windows Vista recovery media	optional (extra order number)
Driver and Utility DVD (DUDVD)	optional (extra order number S26361 F2007 E903)
Eco Power Saving Utility	X
Easy Guide on-line user documentation	X
Nero Essentials	X
Norton Internet Security (incl. Firewall) on DUDVD for Microsoft Windows XP	X
SmartCase Logon+	X
Toshiba Bluetooth Stack	X
UMTS watcher	optional with UMTS
DVD playback software	optional
Accessories (order number)	·
AC-adapter	S26391-F408-L300
Case	S26391-F119-L57
Port Replicator	S26391-408-L100
	1st: S26391-F405-L820
Battery	2nd: S26391-F405-L821
Modem adapter set 1: D, UK	S26391-F3145-L10
Modem adapter set 2: SW, NO, FI, DK	S26391-F3145-L20
Modem adapter set 3: CH, A, B, NL, F, I, E, POR	S26391-F3145-L30
http://www.fujitsu-siemens.com/accessories/	
Spare part availability	5 years